

# EL<sup>®</sup>MARK

The Brand of Electricity

## MOVABLE RECESSED SPOTLIGHTS DL81/82F1 SERIES

### GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 15W; 30W; 45W; 60W; 90W
- ∴ Driver: non-isolated driver
- ∴ Colour temperature: 3000K; 4000K
- ∴ Colour body: Black
- ∴ Material: Aluminium
- ∴ Beam angle: 24°
- ∴ CRI: Ra≥80
- ∴ Power factor: 0.5
- ∴ Movable
- ∴ Protection level against moisture and dust: IP44

### FEATURES »

- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction





\*Options with emergency kit

[PRODUCT DETAILS »](#)

| Catalogue number | Watt (W) | Whole fixture lumens (lm) | Colour temp. (K) | Length (mm) | Width (mm) | Height (mm) | Cut hole (mm) | Colour body |
|------------------|----------|---------------------------|------------------|-------------|------------|-------------|---------------|-------------|
| 92DL81F1530/BL   | 15       | 1050                      | 3000             | 138         | 138        | 98          | 120x120       | black       |
| 92DL81F1540/BL   | 15       | 1050                      | 4000             | 138         | 138        | 98          | 120x120       | black       |
| 92DL82F3030/BL   | 30       | 2100                      | 3000             | 176         | 176        | 138         | 160x160       | black       |
| 92DL82F3040/BL   | 30       | 2100                      | 4000             | 176         | 176        | 138         | 160x160       | black       |
| 92DL81F3030/BL   | 2X15     | 2100                      | 3000             | 250         | 138        | 98          | 230x120       | black       |
| 92DL81F3040/BL   | 2X15     | 2100                      | 4000             | 250         | 138        | 98          | 230x120       | black       |
| 92DL82F6030/BL   | 2X30     | 4200                      | 3000             | 325         | 176        | 138         | 310x160       | black       |
| 92DL82F6040/BL   | 2X30     | 4200                      | 4000             | 325         | 176        | 138         | 310x160       | black       |
| 92DL81F4530/BL   | 3X15     | 3150                      | 3000             | 363         | 138        | 98          | 345x120       | black       |
| 92DL81F4540/BL   | 3X15     | 3150                      | 4000             | 363         | 138        | 98          | 345x120       | black       |
| 92DL82F9030/BL   | 3X30     | 6300                      | 3000             | 476         | 176        | 138         | 460x160       | black       |
| 92DL82F9040/BL   | 3X30     | 6300                      | 4000             | 476         | 176        | 138         | 460x160       | black       |

