


LAMP PHOTOMETRIC REPORT

MODEL: 92EL62284265/WH		
POWER: 42W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 4405.9 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2623	2617	2616	2621	2629	2635	2637	2632	0- 10	254.8	254.8	5.78
20	2381	2370	2370	2376	2389	2400	2401	2393	10- 20	709.4	964.2	21.9
30	1852	1832	1826	1838	1859	1875	1878	1871	20- 30	989.3	1953	44.3
40	1185	1169	1164	1172	1193	1204	1206	1201	30- 40	944.6	2898	65.8
50	641.7	629.2	622.2	627.8	640.2	649.3	651.5	649.4	40- 50	690.1	3588	81.4
60	320.2	315.8	312.4	312.4	315.9	320.2	319.2	322.3	50- 60	408.0	3996	90.7
70	189.0	183.9	176.6	181.0	185.5	185.8	182.7	187.8	60- 70	246.0	4242	96.3
80	77.20	71.05	63.76	69.85	74.25	71.70	70.26	72.35	70- 80	132.0	4374	99.3
90	1.293	1.277	1.233	1.293	1.160	1.158	1.125	1.142	80- 90	31.72	4406	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:05 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```