


LAMP PHOTOMETRIC REPORT

MODEL: 92EL67054030/WH		
POWER: 40W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 4297.2 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2925	2837	2780	2846	2914	2872	2833	2877	0- 10	279.9	279.9	6.51
20	2682	2449	2261	2439	2639	2532	2434	2545	10- 20	759.3	1039	24.2
30	2257	1813	1538	1778	2189	1939	1714	1987	20- 30	1013	2052	47.8
40	1688	1113	829.9	1075	1614	1215	991.4	1264	30- 40	970.8	3023	70.3
50	1036	511.4	292.9	492.7	971.8	587.1	370.2	619.2	40- 50	691.0	3714	86.4
60	465.0	189.7	103.3	180.5	428.2	214.2	126.9	223.4	50- 60	353.4	4067	94.7
70	159.9	70.74	46.58	69.67	149.4	82.91	59.50	84.64	60- 70	150.8	4218	98.2
80	50.25	27.46	19.89	27.85	49.05	32.47	25.02	32.00	70- 80	60.43	4279	99.6
90	1.264	0.9992	0.6736	0.9857	1.147	2.582	10.66	2.245	80- 90	18.57	4297	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:07 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```