


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial80/BL		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 373.40 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	243.8	243.7	245.2	245.7	239.5	239.4	238.1	237.8	0- 10	23.68	23.68	6.34
20	209.2	208.2	211.4	212.7	203.0	202.9	200.5	200.2	10- 20	63.36	87.04	23.3
30	160.6	159.7	162.9	165.0	156.0	155.5	152.6	151.6	20- 30	83.82	170.9	45.8
40	109.9	109.2	112.4	113.8	107.4	106.9	104.0	103.1	30- 40	82.90	253.8	68
50	60.92	59.86	61.89	62.34	58.80	59.20	56.87	56.48	40- 50	63.98	317.7	85.1
60	26.13	25.47	26.74	26.82	25.10	25.47	24.25	24.20	50- 60	36.59	354.3	94.9
70	7.665	7.406	8.068	8.231	7.594	7.817	7.329	7.161	60- 70	15.26	369.6	99
80	0.3439	0.3514	0.5321	0.7821	0.7256	0.7343	0.6004	0.3645	70- 80	3.685	373.3	100
90	0.0428	0.0406	0.0382	0.0383	0.0348	0.0325	0.0355	0.0329	80- 90	0.1267	373.4	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:30 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```