


LAMP PHOTOMETRIC REPORT

MODEL: 95Livia90/WH		
POWER: 6W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 497.55 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	408.6	406.1	406.4	407.7	405.8	405.9	408.8	409.7	0- 10	41.45	41.45	8.33
20	298.0	295.6	293.4	298.2	296.5	292.9	296.9	300.5	10- 20	98.45	139.9	28.1
30	198.0	197.9	193.1	197.7	198.7	193.4	192.9	197.1	20- 30	111.8	251.7	50.6
40	120.8	121.1	122.0	123.4	122.9	118.4	120.3	121.3	30- 40	97.48	349.1	70.2
50	67.97	68.72	72.21	72.10	69.92	67.22	70.73	70.49	40- 50	72.17	421.3	84.7
60	34.45	35.52	38.11	37.44	35.23	34.00	36.63	36.40	50- 60	46.30	467.6	94
70	11.59	12.59	14.19	13.42	11.52	10.97	11.90	12.22	60- 70	23.17	490.8	98.6
80	1.641	1.818	1.988	1.937	1.734	1.572	1.519	1.542	70- 80	5.997	496.8	99.8
90	0.0677	0.0666	0.0763	0.0778	0.0542	0.0557	0.0599	0.0587	80- 90	0.7826	497.6	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:19 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```